



	WATER CONNECTION 3/4" GAS		DRAINING PIPE Ø 24mm		ELECTRICAL SUPPLY
--	----------------------------------	--	-----------------------------	--	--------------------------

TECHNICAL DATA	STD		
EXTERNAL DIMENSIONS			
width	400 mm		
depth	495 mm		
height	595 mm		
WEIGHT	28 kg		
VOLTAGE	230V 50Hz		
POWER REQUIRED	2590 W		
WATER HARDNESS	2-8 °F		
INLET WATER PRESSURE	200-400 kPa		
CROCKERY DIMENSIONS			
plates diameter	--- mm		
dishes max. height	195 mm		
RACK DIMENSIONS			
RACK EQUIPMENT	2X10730- 1X10728 - 1X15060		
WASHING CYCLES (s)	1<90>	2<120>	3<180>
WATER SUPPLY 55°C			
racks/h(*) ⁽¹⁾	38	30	20
WATER SUPPLY 10°C			
racks/h(*) ⁽¹⁾	17	17	17
WATER CONSUMPTION / CYCLE (water pressure 200kPa)	1.4 L		
BOILER CAPACITY	2.5 L		
BOILER HEATING ELEMENT	2400 W		
RINSING TEMPERATURE (SET)	85°C		
TANK CAPACITY	9.5 L		
TANK HEATING ELEMENT	1250 W		
TANK TEMPERATURE	55°C		
PUMP POWER	190 W (120 L/min ^{***})		
DRAIN PUMP (optional)	25 W h MAX drainig 0.8m (40 L/min ^{***})		
NOISE	60.6±0.7 dB(A)		

(*) STANDARD TERMOSTOP

(***) MAXIMUM FLOW RATE

⁽¹⁾ In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.