



| | | | | | |
|--|---------------------------|--|----------------------|--|-------------------|
| | WATER CONNECTION 3/4" GAS | | DRAINING PIPE Ø 24mm | | ELECTRICAL SUPPLY |
|--|---------------------------|--|----------------------|--|-------------------|

| TECHNICAL DATA | STD |
|---|--|
| EXTERNAL DIMENSIONS | |
| width | 400 mm |
| depth | 495 mm |
| height | 585 mm |
| WEIGHT | 28 kg |
| VOLTAGE | 230V 50Hz |
| POWER REQUIRED | 2590 W |
| WATER HARDNESS | 2-8 °F |
| INLET WATER PRESSURE | 200-400 kPa |
| CROCKERY DIMENSIONS | |
| plates diameter | --- mm |
| dishes max. height | 195 mm |
| RACK DIMENSIONS | |
| RACK EQUIPMENT | 2X10730- 1X10728 - 1X15060 |
| WASHING CYCLES (s) | 1 (120) |
| WATER SUPPLY 55°C | |
| racks/h(*) ⁽¹⁾ | 30 |
| WATER SUPPLY 10°C | |
| racks/h(*) ⁽¹⁾ | 18 |
| WATER CONSUMPTION / CYCLE (water pressure 200kPa) | 1.4 L |
| BOILER CAPACITY | 2.5 L |
| BOILER HEATING ELEMENT | 2400 W |
| RINSING TEMPERATURE (SET) | 85°C |
| TANK CAPACITY | 9.5 L |
| TANK HEATING ELEMENT | 1250 W |
| TANK TEMPERATURE | 55°C |
| PUMP POWER | 190 W (120 L/min ^{***}) |
| DRAIN PUMP (optional) | 25 W h MAX drainig 0.8m (40 L/min ^{***}) |
| NOISE | 60.6±0.7 dB(A) |

(*) STANDARD TERMOSTOP

(***) MAXIMUM FLOW RATE

(¹) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.