


WATER CONNECTION 3/4" GAS

DRAINING PIPE Ø 24mm

ELECTRICAL SUPPLY

TECHNICAL DATA		STD		
EXTERNAL DIMENSIONS				
width		450 mm		
depth		535 mm		
height		710 mm		
WEIGHT				
		37 kg		
VOLTAGE				
		230V 50Hz		
POWER REQUIRED				
		2590 W		
WATER HARDNESS				
		2-8 °F		
INLET WATER PRESSURE				
		200-400 kPa		
CROCKERY DIMENSIONS				
plates diameter (LS version)		295mm		
dishes max. height		305mm		
RACK DIMENSIONS				
		400X400mm		
RACK EQUIPMENT				
		2XC121 - 1X10728 - 1X15060		
WASHING CYCLES (s)				
		1<90>	2<120>	3<180>
WATER SUPPLY 55°C				
racks/h(*) ⁽¹⁾		31	30	20
WATER SUPPLY 10°C				
racks/h(*) ⁽¹⁾		14	14	14
WATER CONSUMPTION / CYCLE (water pressure 200kPa)				
		1.8 L		
BOILER CAPACITY				
		3.4 L		
BOILER HEATING ELEMENT				
		2400 W		
RINSING TEMPERATURE (SET)				
		85°C		
TANK CAPACITY				
		14.5 L		
TANK HEATING ELEMENT				
		1250 W		
TANK TEMPERATURE (SET)				
		55°C		
PUMP POWER				
		190 W (120 L/min ^{***})		
DRAIN PUMP (optional)				
		25 W h MAX drainig 0.8m (40 L/min ^{***})		
NOISE				
		60.6 (dB(A)±0.7)		

(*) STANDARD TERMOSTOP
(*) MAXIMUM FLOW RATE**

⁽¹⁾ In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.