



	WATER CONNECTION 3/4" GAS		DRAINING PIPE Ø 24mm		ELECTRICAL SUPPLY
--	---------------------------	--	----------------------	--	-------------------

TECHNICAL DATA	STD
<b>EXTERNAL DIMENSIONS</b>	
width	450 mm
depth	535 mm
height	700 mm
<b>WEIGHT</b>	37 kg
<b>VOLTAGE</b>	230V 50Hz
<b>POWER REQUIRED</b>	2590 W
<b>WATER HARDNESS</b>	2-8 °F
<b>INLET WATER PRESSURE</b>	200-400 kPa
<b>CROCKERY DIMENSIONS</b>	
plates diameter (LS version)	295mm
dishes max. height	305mm
<b>RACK DIMENSIONS</b>	400X400mm
<b>RACK EQUIPMENT</b>	2XC121 - 1X10728 - 1X15060
<b>WASHING CYCLES</b> (s)	1 (120)
<b>WATER SUPPLY 55°C</b>	
racks/h(*) <sup>(1)</sup>	30
<b>WATER SUPPLY 10°C</b>	
racks/h(*) <sup>(1)</sup>	16
<b>WATER CONSUMPTION / CYCLE</b> (water pressure 200kPa)	1.8 L
<b>BOILER CAPACITY</b>	3.4 L
<b>BOILER HEATING ELEMENT</b>	2400 W
<b>RINSING TEMPERATURE (SET)</b>	85°C
<b>TANK CAPACITY</b>	14.5 L
<b>TANK HEATING ELEMENT</b>	1250 W
<b>TANK TEMPERATURE (SET)</b>	55°C
<b>PUMP POWER</b>	190 W (120 L/min <sup>***</sup> )
<b>DRAIN PUMP (optional)</b>	25 W h MAX drainig 0.8m (40 L/min <sup>***</sup> )
<b>NOISE</b> (dB(A)±0.7)	60.6(CF) 61.2 (LS)

(\*) STANDARD TERMOSTOP

(\*\*\*) MAXIMUM FLOW RATE

(<sup>1</sup>) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.