



	WATER CONNECTION 3/4" GAS		DRAINING PIPE Ø 24mm		ELECTRICAL SUPPLY
--	----------------------------------	--	-----------------------------	--	--------------------------

TECHNICAL DATA	STD
EXTERNAL DIMENSIONS	
width	415mm
depth	465mm
height	670mm
WEIGHT	30 kg
VOLTAGE	230V 50Hz
POWER REQUIRED	2590 W
WATER HARDNESS	2-8 °F
INLET WATER PRESSURE	200-400 kPa
CROCKERY DIMENSIONS	
plates diameter	---
dishes max. height	270mm
RACK DIMENSIONS	350X350
RACK EQUIPMENT	2X10730- 1X10728 - 1X15060
WASHING CYCLES (<s>)	1<120>
WATER SUPPLY 55°C	
racks/h(*) ⁽¹⁾	30
WATER SUPPLY 10°C	
racks/h(*) ⁽¹⁾	18
WATER CONSUMPTION / CYCLE (water pressure 200kPa)	1.4 L
BOILER CAPACITY	3 L
BOILER HEATING ELEMENT	2400 W
RINSING TEMPERATURE (SET)	85°C
TANK CAPACITY	12 L
TANK HEATING ELEMENT	1250 W
TANK TEMPERATURE (SET)	55°C
PUMP POWER	190 W (<120 L/min***)
DRAIN PUMP (optional)	25 W h MAX 0.8m (<40 L/min***)
NOISE	60.6±0.7 dB(A)

(*) STANDARD TERMOSTOP

(***) MAXIMUM FLOW RATE

(¹) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.