



	ELECTRICAL SUPPLY
	WATER CONNECTION 3/4" GAS
	DRAINING PIPE Ø 24mm

TECHNICAL DATA	STANDARD			
EXTERNAL DIMENSIONS				
width	595 mm			
depth	610 mm			
height	845 mm			
WEIGHT	61 kg			
VOLTAGE	400V 3N 50Hz			
POWER REQUIRED	5150 W			
WATER HARDNESS	2-8 °F			
INLET WATER PRESSURE	200-400 kPa			
CROCKERY DIMENSIONS				
plates diameter	325 mm			
glasses max. height	310 mm			
RACK DIMENSIONS	500X500 mm			
RACK EQUIPMENT	1XC40 - 1XC44 - 1X15060			
WASHING CYCLES (s)	1<60>	2<90>	3<120>	4<180>
WATER SUPPLY 55°C				
racks/h(*) ⁽¹⁾	60	40	30	20
WATER SUPPLY 10°C				
racks/h(*) ⁽¹⁾	20	20	20	20
WATER CONSUMPTION / CYCLE (water pressure 200kPa)	2.3 L			
BOILER CAPACITY	5.7 L			
BOILER HEATING ELEMENT	4500 W			
RINSING TEMPERATURE (SET)	85°C			
TANK CAPACITY	27 L			
TANK HEATING ELEMENT	2700 W			
TANK TEMPERATURE (SET)	55°C			
PUMP POWER	650 W (340 L/min ^{***})			
DRAIN PUMP (optional)	25 W h MAX drainig 0.8m (40 L/min ^{***})			
NOISE	59.3 dB(A)			

(*) STANDARD TERMOSTOP

(***) MAXIMUM FLOW RATE

(¹) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.