



WATER CONNECTION 3/4" GAS



DRAINING Ø 24mm



ELECTRICAL SUPPLY

TECHNICAL DATA				
<b>EXTERNAL DIMENSIONS</b>				
width	460 mm			
depth	550 mm			
height	780 mm			
<b>WEIGHT(basic version)</b>	48,5 kg			
<b>VOLTAGE</b>	230V 50Hz			
<b>POWER REQUIRED</b>	3250 W			
<b>WATER HARDNESS</b>	2-8 °f			
<b>INLET WATER PRESSURE</b>	200-400 kPa			
<b>CROCKERY DIMENSIONS</b>				
plates diameter	310 mm			
size allowed	310 mm			
<b>RACK DIMENSIONS</b>	400X400 mm			
<b>RACK EQUIPMENT</b>	2XC121 - 1X10728 - 1X15060			
<b>WASHING CYCLES</b> (s)	1 (60)	2 (90)	3 (120)	4 (180)
<b>WATER SUPPLY 55°C</b>				
racks/h(*) <sup>(†)</sup>	--	--	--	--
<b>WATER SUPPLY 10°C</b>				
racks/h(*) <sup>(†)</sup>	28	28	21	16
<b>WATER CONSUMPTION / CYCLE</b> (water pressure 200kPa)	1,8 L			
<b>BOILER CAPACITY</b>	5,5 l			
<b>BOILER HEATING ELEMENT</b>	3000 W			
<b>RINSING TEMPERATURE (SET)</b>	70°C		85°C	
<b>TANK CAPACITY</b>	7 L			
<b>TANK HEATING ELEMENT</b>	1100 W			
<b>TANK TEMPERATURE (SET)</b>	55°C			
<b>PUMP POWER</b>	250 W (150 L/min <sup>***</sup> )			
<b>DRAIN PUMP (optional)</b>	25 W h max draining 0,8 m (40 L/min <sup>***</sup> )			
<b>NOISE</b>	59.9±0.7 dB(A)			

(\*) STANDARD TERMOSTOP

(\*\*\*) MAXIMUM FLOW RATE

(†) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.