

WATER CONNECTION 3/4" GAS




DRAINING Ø 24mm



ELECTRICAL SUPPLY

PIEDINO "MARINA" "MARINA" FOOT

TECHNICAL DATA				
EXTERNAL DIMENSIONS				
width	600 mm			
depth	610 mm			
height	850 mm			
WEIGHT	63.5 kg			
VOLTAGE	400V 3N 50Hz (380/400V 3 60Hz "Marina")			
POWER REQUIRED	5150 W			
WATER HARDNESS	2-8 °f			
INLET WATER PRESSURE	200-400 kPa			
CROCKERY DIMENSIONS				
plates diameter	340 mm			
dishes max. height	325 mm/GASTRONORM			
RACK DIMENSION	500X500 mm			
RACK EQUIPMENT	1XC40 - 1XC44 - 1X15060			
WASHING CYCLES (sec)	1 (60)	2 (90)	3 (120)	4 (180)
WATER SUPPLY 55°C				
racks/h(*) ⁽¹⁾	60	40	30	20
WATER SUPPLY 10°C				
racks/h(*) ⁽¹⁾	24	20	20	20
WATER CONSUMPTION / CYCLE (water pressure 200kPa)	2.3 l			
BOILER CAPACITY	5.7 l			
BOILER HEATING ELEMENT	4500 W			
RINSING TEMPERATURE (SET)	70°C		85°C	
TANK CAPACITY	16.5 l			
TANK HEATING ELEMENT	2700 W (2230W "Marina")			
TANK TEMPERATURE (SET)	55°C			
PUMP POWER	650 W (340 l/min ^{***})			
DRAIN PUMP (optional)	25 W h MAX draining 0.8 m (40 l/min ^{***})			
NOISE	61,3±0.7 dB(A)			



(*) STANDARD TERMOSTOP

(***) MAXIMUM FLOW RATE

(¹) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.