



	WATER CONNECTION 3/4" GAS		DRAINING PIPE Ø 24mm		ELECTRICAL SUPPLY
--	----------------------------------	--	-----------------------------	--	--------------------------

TECHNICAL DATA	STANDARD				
EXTERNAL DIMENSIONS					
width	590 mm				
depth	600 mm				
height	850 mm				
WEIGHT	56,5 kg				
VOLTAGE	400V 3N 50Hz				
POWER REQUIRED	5150 W				
WATER HARDNESS	2-8 °F				
INLET WATER PRESSURE	200-400 kPa				
CROCKERY DIMENSIONS					
plates diameter	345 mm				
dishes max. height	320 mm				
RACK DIMENSIONS	500X500 mm				
RACK EQUIPMENT	1XC40 = 1XC44 = 1X15060				
WASHING CYCLES (s)	1(60)	2(90)	3(120)	4(180)	-----
WATER SUPPLY 55°C					
racks/h(*) ⁽¹⁾	60	40	30	20	--
WATER SUPPLY 10°C					
racks/h(*) ⁽¹⁾	20	20	20	20	--
WATER CONSUMPTION / CYCLE (water pressure 200kPa)	2.3 L				
BOILER CAPACITY	5.7 L				
BOILER HEATING ELEMENT	4500 W				
RINSING TEMPERATURE (SET)	85°C				
TANK CAPACITY	29 L				
TANK HEATING ELEMENT	2700 W				
TANK TEMPERATURE (SET)	55°C				
PUMP POWER	650 W (340 L/min ^{***})				
DRAIN PUMP (optional)	25 W h MAX draining 0.8m (40 L/min ^{***})				
NOISE	63 dB(A)				

(*) STANDARD TERMOSTOP

(***) MAXIMUM FLOW RATE

¹⁾ In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.