



	<b>WATER CONNECTION 3/4" GAS</b>		<b>DRAINING PIPE Ø 24mm</b>		<b>ELECTRICAL SUPPLY</b>
--	----------------------------------	--	-----------------------------	--	--------------------------

TECHNICAL DATA		STD	
<b>EXTERNAL DIMENSIONS</b>			
width		590 mm	
depth		600 mm	
height		850 mm	
<b>WEIGHT</b>		56.5 kg	
<b>VOLTAGE</b>		400V 3N 50Hz (230/60 - 230/3/60)	
<b>POWER REQUIRED</b>		5150 W	
<b>WATER HARDNESS</b>		2-8 °F	
<b>INLET WATER PRESSURE</b>		200-400 kPa	
<b>CROCKERY DIMENSIONS</b>			
plates diameter		345 mm	
dishes max. height		320 mm	
<b>RACK DIMENSIONS</b>		500X500 mm	
<b>RACK EQUIPMENT</b>		1XC40 - 1XC44 - 1X15060	
<b>WASHING CYCLES</b>	(s)	1 (120)	2 (180)
<b>WATER SUPPLY 55°C</b>			
racks/h(*) <sup>(1)</sup>		30	20
<b>WATER SUPPLY 10°C</b>			
racks/h(*) <sup>(1)</sup>		21	20
<b>WATER CONSUMPTION / CYCLE</b> (water pressure 200kPa)		2.3 L	
<b>BOILER CAPACITY</b>		5.7 L	
<b>BOILER HEATING ELEMENT</b>		4500 W	
<b>RINSING TEMPERATURE (SET)</b>		85°C	
<b>TANK CAPACITY</b>		29 L	
<b>TANK HEATING ELEMENT</b>		2700 W	
<b>TANK TEMPERATURE (SET)</b>		55°C	
<b>PUMP POWER</b>		650 W (340 L/min <sup>***</sup> )	
<b>DRAIN PUMP (optional)</b>		25 W h MAX drainig 0.8m (40 L/min <sup>***</sup> )	
<b>NOISE</b>		63 dB(A)	

(\*) STANDARD TERMOSTOP

(\*\*\*) MAXIMUM FLOW RATE

<sup>1)</sup> In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.