



|  |                           |
|--|---------------------------|
|  | WATER CONNECTION 3/4" GAS |
|  | DRAINING PIPE Ø 28mm      |
|  | ELECTRICAL SUPPLY         |



\*\*\* MIN 130-MAX 200 mm

| TECHNICAL DATA                                    |   |        |           |           |      |
|---|---|--------|-----------|-----------|------|
| <b>EXTERNAL DIMENSIONS</b>                        |   |        |           |           |      |
| width   | 720 mm                                  |        |           |           |      |
| depth   | 735 mm                                  |        |           |           |      |
| height  | 1445/1880(open hood) mm                 |        |           |           |      |
| WEIGHT(basic version)                             | 115 kg                                  |        |           |           |      |
| VOLTAGE   | 400V 3N 50Hz (380/400V 3 60Hz "Marina") |        |           |           |      |
| POWER REQUIRED                                    | 10490 W                                 |        |           |           |      |
| WATER HARDNESS                                    | 2-8 °F                                  |        |           |           |      |
| INLET WATER PRESSURE                              | 200-400 kPa                             |        |           |           |      |
| <b>CROCKERY DIMENSIONS</b>                        |   |        |           |           |      |
| plates diameter                                   | 410 mm                                  |        |           |           |      |
| trays max. dimension                              | GASTRONORM 1/1 (530x325)                |        |           |           |      |
| RACK DIMENSION                                    | 500X500 mm                              |        |           |           |      |
| RACK EQUIPMENT                                    | 2XC40 - 1XC44 - 2X15060                 |        |           |           |      |
| WASHING CYCLES (s)                                | 1 (50)                                  | 2 (90) | 3 (180)** | 4 (630)** | ---- |
| <b>WATER SUPPLY 55°C</b>                          |   |        |           |           |      |
| racks/h(*) <sup>(1)</sup>                         | 60                                      | 40     | 20        | 5         | ---- |
| <b>WATER SUPPLY 10°C</b>                          |   |        |           |           |      |
| racks/h(*) <sup>(1)</sup>                         | 30                                      | 30     | 20        | 5         | ---- |
| WATER CONSUMPTION / CYCLE (water pressure 200kPa) | 2.8 L                                   |        |           |           |      |
| BOILER CAPACITY                                   | 10 L                                    |        |           |           |      |
| BOILER HEATING ELEMENT                            | 9000 W                                  |        |           |           |      |
| RINSING TEMPERATURE (SET)                         | 85°C                                    |        | 90°C      |           |      |
| TANK CAPACITY                                     | 42 L                                    |        |           |           |      |
| TANK HEATING ELEMENT                              | 2700 W                                  |        |           |           |      |
| TANK TEMPERATURE (SET)                            | 55°C                                    |        | 70°C      |           |      |
| PUMPS POWER                                       | 1490 W (800 L/min***)                   |        |           |           |      |
| DRAIN PUMP (optional)                             | 25 W (40 L/min***)                      |        |           |           |      |
| NOISE   | 66,4±0.7 dB(A)                          |        |           |           |      |

**(\*) STANDARD TERMOSTOP (\*\*) WITH 70°C IN TANK (\*\*\*) MAXIMUM FLOW RATE**

(1) In case of cold water inlet and/or in case of many consecutive wash cycles, the heating times of the final rinse and wash could be extended until the optimum temperature is reached. As a result, the total time of the wash cycle may increase.