



	<b>WATER CONNECTION 3/4" GAS</b>
	<b>DRAINING PIPE Ø 28mm</b>
	<b>ELECTRICAL SUPPLY</b>



<b>EXIT AIR TEMPERATURE :</b> <b>25°C</b>
<b>HUMIDITY:</b> <b>60%</b>
<b>AIR FLOW RATE:</b> <b>105 m³/h</b>
<b>HEAT RECOVERY PER HOUR:</b> <b>6 kWh</b> (VALUES CALCULATED ON THE BASIS OF THE SHORTEST CYCLE)

TECHNICAL DATA						
<b>EXTERNAL DIMENSIONS</b>						
width	720 mm					
depth	735 mm					
height	2095 mm					
WEIGHT(basic version)	145 kg					
VOLTAGE	400V 3N 50Hz					
POWER REQUIRED	10490 W					
WATER HARDNESS	< 8 °f					
WATER CONDUCTIVITY	> 200 µS\cm					
INLET WATER PRESSURE	200-400 kPa					
<b>CROCKERY DIMENSIONS</b>						
plates diameter	410 mm					
trays max. dimension	GASTRONORM 1/1 (530x325)					
RACK DIMENSION	500X500 mm					
RACK EQUIPMENT	2XC40 - 1XC44 - 2X15060					
WASHING CYCLES	(s)	1 (50)	2 (90)	3 (120)	4 (180)	5 (180**) 6 (630**)
<b>WATER SUPPLY 10°C</b>						
racks/h(*) (1)	55	40	30	20	20	5
WATER CONSUMPTION / CYCLE	2,6 L					
BOILER CAPACITY	15 L					
BOILER HEATING ELEMENT	9000 W					
RINSING TEMPERATURE (SET)	85°C			90°C		
TANK CAPACITY	42 L					
TANK HEATING ELEMENT	2700 W					
TANK TEMPERATURE (SET)	55°C					
PUMPS POWER washing / rinsing	1490 (800 L/min***)/250 W					
DRAIN PUMP (optional)	25 W (40 L/min***)					
NOISE	66.4±0.7 dB(A)					

**(\*) STANDARD TERMOSTOP (\*\*) WITH 70°C IN TANK (\*\*\*)MAXIMUM FLOW RATE**

(†) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.