


**TECHNICAL DATA**
**EXTERNAL DIMENSIONS**

width	720 mm
depth	735 mm
height	1445/1880(open hood) mm

**WEIGHT(basic version)**

115 kg

**VOLTAGE**

400V 3N 50Hz (380/400V 3 60Hz "Marina")

**POWER REQUIRED**

10490 W

**WATER HARDNESS**

2-8 °F

**INLET WATER PRESSURE**

200-400 kPa

**CROCKERY DIMENSIONS**

plates diameter	410 mm
trays max. dimension	GASTRONORM 1/1 (530x325)

**RACK DIMENSION**

500X500 mm

**RACK EQUIPMENT**

2XC40 - 1XC44 - 2X15060

**WASHING CYCLES**

	(s)	1 (50)	2 (90)	3 (120)	4 (180)	----
--	-----	--------	--------	---------	---------	------

**WATER SUPPLY 55°C**

racks/h(*) <sup>(1)</sup>	60	40	30	20	----
---------------------------	----	----	----	----	------

**WATER SUPPLY 10°C**

racks/h(*) <sup>(1)</sup>	30	30	30	20	----
---------------------------	----	----	----	----	------

**WATER CONSUMPTION / CYCLE  
(water pressure 200kPa)**

2.8 L

**BOILER CAPACITY**

10 L

**BOILER HEATING ELEMENT**

9000 W

**RINSING TEMPERATURE (SET)**

85°C

**TANK CAPACITY**

42 L

**TANK HEATING ELEMENT**

2700 W

**TANK TEMPERATURE (SET)**

55°C

**PUMPS POWER**

 1490 W (800 L/min<sup>\*\*\*</sup>)

**DRAIN PUMP (optional)**

 25 W (40 L/min<sup>\*\*\*</sup>)

**NOISE**

66,4±0.7 dB(A)

(\*) STANDARD TERMOSTOP

(\*\*\*) MAXIMUM FLOW RATE

(<sup>1</sup>) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.