



	WATER CONNECTION 3/4" GAS
	DRAINING PIPE Ø 28mm
	ELECTRICAL SUPPLY


**TECHNICAL DATA**
**EXTERNAL DIMENSIONS**

width	720 mm
depth	735 mm
height	2095 mm

**WEIGHT(basic version)**

145 kg

**VOLTAGE**

400V 3N 50Hz

**POWER REQUIRED**

9900 W

**WATER HARDNESS**
 $< 8 \text{ } ^\circ\text{f}$ 
**WATER CONDUCTIVITY**
 $> 200 \text{ } \mu\text{S/cm}$ 
**INLET WATER PRESSURE**

200-400 kPa

**CROCKERY DIMENSIONS**

plates diameter 410 mm

**trays max. dimension**

GASTRONORM 1/1 (530x325)

**RACK DIMENSION**

500X500 mm

**RACK EQUIPMENT**

2XC40 - 1XC44 - 2X15060

**WASHING CYCLES (sec)**

0(21+680) (**)	1 (50)	2 (90)	3 (120)	4 (180)	5 (300)
----------------	--------	--------	---------	---------	---------

**WATER SUPPLY 10°C**
**racks/h(\*) (1)**

/	40	40	30	20	12
---	----	----	----	----	----

**WATER CONSUMPTION / CYCLE**

3,5 l

**BOILER CAPACITY**

15 l

**BOILER HEATING ELEMENT**

9000 W

**RINSING TEMPERATURE (SET)**

70°C-90°C(\*\*) 82°C

**TANK CAPACITY**

20 l

**TANK HEATING ELEMENT**

2700 W

**TANK TEMPERATURE (SET)**

50°C-70°C(\*\*) 60°C

**PUMPS POWER washing/rinsing**

900W (500 l/min\*\*\*) /250 W

**DRAIN PUMP**

25W (40 l/min\*\*\*)

**NOISE**

63.6±0.7 dB(A)

 EXIT AIR TEMPERATURE :  
**25°C**

 HUMIDITY:  
**60%**

 AIR FLOW RATE:  
**105 m³/h**

 HEAT RECOVERY PER HOUR:  
**6 kWh**

(VALUES CALCULATED ON THE BASIS OF THE SHORTEST CYCLE)

**(\*) STANDARD TERMOSTOP / (\*\*\*) MAXIMUM FLOW RATE / (\*\*\*) CUSTOM CYCLE**

(†) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.