



	<b>ELECTRICAL SUPPLY</b>
	<b>WATER CONNECTION 3/4" GAS</b>
	<b>DRAINING PIPE Ø 24mm</b>

TECHNICAL DATA					
<b>EXTERNAL DIMENSIONS</b>					
width	600 mm				
depth	700 mm				
height	1380 mm				
WEIGHT(basic version)	99 kg				
VOLTAGE	400V 3N 50Hz				
POWER REQUIRED	10120 W				
WATER HARDNESS	2-8 °F				
INLET WATER PRESSURE	200-400 kPa				
<b>CROCKERY DIMENSIONS</b>					
plates diameter	---				
size allowed	440 mm				
RACK DIMENSIONS	500X610 mm				
RACK EQUIPMENT	1XC132 - 1X575005 - 1XC86/A - 1X575010				
WASHING CYCLES	(s)	1 (60)	2 (120)	3 (180)	4 (300)
<b>WATER SUPPLY 55°C</b>					
racks/h(*) <sup>(1)</sup>	60	30	20	12	
<b>WATER SUPPLY 10°C</b>					
racks/h(*) <sup>(1)</sup>	30	30	20	12	
WATER CONSUMPTION / CYCLE	2.6 l				
BOILER CAPACITY	15 l				
BOILER HEATING ELEMENT	9000 W				
RINSING TEMPERATURE (SET)	85°C				
TANK CAPACITY	25 l				
TANK HEATING ELEMENT	2700 W				
TANK TEMPERATURE (SET)	55°C				
PUMP POWER	1120 W (630 l/min <sup>***</sup> )				
RINSING PUMP POWER	250 W (150 l/min <sup>***</sup> )				
DRAIN PUMP (optional)	190 W (120 l/min <sup>***</sup> )				
NOISE	63.8 dB(A)				

(\*) STANDARD TERMOSTOP

(\*\*\*) MAXIMUM FLOW RATE

(<sup>1</sup>) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.