



| TECHNICAL DATA             |  |
|----------------------------|--|
| <b>EXTERNAL DIMENSIONS</b> |  |
| width                      | 690 mm                                       |
| depth                      | 800 mm                                       |
| height                     | 2165/2270mm (door open)                      |
| WEIGHT(basic version)      | 165 kg                                       |
| VOLTAGE                    | 400V 3N 50Hz                                 |
| POWER REQUIRED             | 8000 W                                       |
| WATER HARDNESS             | < 8 °F                                       |
| WATER CONDUCTIVITY         | > 200 µS/cm                                  |
| INLET WATER PRESSURE       | 200-400 kPa                                  |
| <b>CROCKERY DIMENSIONS</b> |  |
| size allowed               | 805 mm                                       |
| RACK DIMENSIONS            | 550X665 mm                                   |
| RACK EQUIPMENT             | 1XC86/A - 1XC87/B - 1XC97/A - 1XC100         |
| WASHING CYCLES (s)         | 1 (180)   2 (300)   3 (420)   4 (540)   ---- |
| <b>WATER SUPPLY 55°C</b>   |  |
| racks/h(*) <sup>(1)</sup>  | --   --   --   --   --                       |
| <b>WATER SUPPLY 10°C</b>   |  |
| racks/h(*) <sup>(1)</sup>  | 13   12   8   6,5   --                       |
| WATER CONSUMPTION / CYCLE  | 4,2 l  |
| BOILER CAPACITY            | 15 l   |
| BOILER HEATING ELEMENT     | 6000 W                                       |
| RINSING TEMPERATURE (SET)  | 85°C   |
| TANK CAPACITY              | 50 l   |
| TANK HEATING ELEMENT       | 3000 W                                       |
| TANK TEMPERATURE (SET)     | 60°C   |
| WASHING PUMP POWER         | 2000 W (810 l/min <sup>***</sup> )           |
| RINSING PUMP POWER         | 250 W (150 l/min <sup>***</sup> )            |
| DRAIN PUMP (optional)      | 190 W (120 l/min <sup>***</sup> )            |
| ACOUSTIC PRESSURE          | 63.8 dB(A)                                   |

(\*) STANDARD TERMOSTOP (CAN NOT BE DISABLED)

(\*\*\*) MAXIMUM FLOW RATE

- STANDARD ENERGY SAVING (CAN NOT BE DISABLED)

<sup>(1)</sup> In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.