


TECHNICAL DATA
EXTERNAL DIMENSIONS

width	1490 mm
depth	885 mm
height	2307 mm

WEIGHT(basic version)

362 kg

VOLTAGE

400V 3N 50Hz

POWER REQUIRED

14800 W

WATER HARDNESS

< 8 °F

WATER CONDUCTIVITY

> 200 µS/cm

INLET WATER PRESSURE

200-400 kPa

CROCKERY DIMENSIONS

size allowed	820 mm
---------------------	--------

RACK DIMENSIONS

1350X725 mm

RACK EQUIPMENT

1XC86/A - 1XC97/A - 1X93600

WASHING CYCLES

(min)

1 (4,5)

2 (7,5)

3 (10,5)

4 (13,5)

WATER SUPPLY 10°C

racks/h(*)⁽¹⁾	13	8	5	4
---------------------------------	----	---	---	---

WATER CONSUMPTION / CYCLE

8,6 L

BOILER CAPACITY

20 L

BOILER HEATING ELEMENT

9000 W

RINSING TEMPERATURE (SET)

85°C

TANK CAPACITY

148 L

TANK HEATING ELEMENT

9000 W

TANK TEMPERATURE (SET)

55°C

WASHING PUMP POWER

 2900 W (950 l/min^{***}) x 2

RINSING PUMP POWER

 250 W (150 l/min^{***}) x 2

DRAIN PUMP (optional)

 190 W (120 l/min^{***})

ACOUSTIC PRESSURE

71,9 dB(A)

(*) STANDARD THERMOSTOP

(***) MAXIMUM FLOW RATE

(¹) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.