



	WATER CONNECTION 3/4" GAS
	DRAINING PIPE Ø 28mm
	ELECTRICAL SUPPLY

HEAT RECOVERY PER HOUR: (Values calculated on the basis of the shortest cycle)
2 kWh

TECHNICAL DATA	CLEAN WATER(**)	PARTIAL DRAINING							CLEAN WATER(**)	
EXTERNAL DIMENSIONS										
width										
depth										
height										
WEIGHT(basic version)										
VOLTAGE										
POWER REQUIRED										
WATER HARDNESS										
INLET WATER PRESSURE										
CROCKERY DIMENSIONS										
useful opening (H)										
RACK DIMENSIONS										
RACK EQUIPMENT										
WASHING CYCLES (s)	0 ^(***) (21+680)	H1 (180)	H2 (630)	1(60)	2(120)	3(180)	4(60)	5(120)	6(180)	7(360)
WATER SUPPLY 55°C										
racks/h ^(*) (¹)	/	---	---	---	---	---	---	---	---	---
WATER SUPPLY 10°C										
racks/h ^(*) (¹)	/	4	4	24	24	20	28	28	12	10
WATER CONSUMPTION/CYCLE	/	7 l	3,5 l	DISHES 3,5 l			GLASSES 3,5 l		CLEAN WATER 7,0 l	
WATER CONDUCTIVITY										
BOILER CAPACITY										
BOILER HEATING ELEMENT										
RINSING TEMPERATURE (SET)	0 ^(***) (70+90°C)	90°C	87°C	82°C			70°C		82°C	
TANK CAPACITY	10 l	7 l	10 l	10 l					7 l	
TANK HEATING ELEMENT										
TANK TEMPERATURE (SET)	0 ^(***) (50+70°C)	75°C	70°C	60°C						
washing/rinsing PUMPS										
DRAIN PUMP										
NOISE										

(*) STANDARD TERMOSTOP/ (**) TOTAL DRAINING EVERY CYCLE / (***) CUSTOM CYCLE

(¹) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.