



	WATER CONNECTION 3/4" G
	DRAINING 15/16 inch
	ELECTRICAL SUPPLY

TECHNICAL DATA						
EXTERNAL DIMENSIONS						
width	(inch)	28 3/8"				
depth	(inch)	28 15/16"				
height	(inch)	56 7/8" / 74 1/16"				
WEIGHT(basic version)	(lbs)	253,5				
VOLTAGE		220-240 V 3 ph 60Hz				
POWER REQUIRED	(W)	10750 W				
WATER HARDNESS		2 - 8 °F				
INLET WATER PRESSURE		20 - 95 psi (170 - 620 kPa)				
CROCKERY DIMENSIONS						
plates diameter	(inch)	16 1/8"				
tray max. dimension	(inch)	GASTRONORM 1/1				
RACK DIMENSIONS	(inch)	20x20"				
RACK EQUIPMENT		2xC40 - 1xC44 - 2x15060				
WASHING CYCLES	(s)	1 (120)	2 (180)	3 (240)	4 (300)	5 (360)
WATER SUPPLY 131°F						
racks/h(*) ⁽¹⁾		30	20	15	12	10
WATER SUPPLY 50°F						
racks/h(*) ⁽¹⁾		20	20	15	12	10
WATER CONSUMPTION / CYCLE (water pressure 200kPa)	[gal(US)]	0,69				
BOOSTER CAPACITY	[gal(US)]	3,96				
BOILER HEATING ELEMENT	(W)	9000 W				
RINSING TEMPERATURE (SET)		185°F				
RINSING PRESSURE		104 - 172 kPa (15 - 25 psi)				
TANK CAPACITY	[gal(US)]	11,1				
TANK HEATING ELEMENT	(W)	2700 W				
TANK TEMPERATURE (SET)		160°F				
PUMP POWER	(W)	1750 W				
DRAIN PUMP		43 W h max draining 31 1/2" (10,78 gal(US))				
NOISE		66,4±0.7 dB(A)				

(*) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.

(*) STANDARD TERMOSTOP

(***) MAXIMUM FLOW RATE